

MAIN FEATURES:

- Efficiency Level V
- MTBF – 100 000h
- Universal AC input / Full range
- 2 years warranty period



NY30-2424-EU

Output	DC Voltage	24V
	Rated Current	1A
	Current Range	0 ~ 1A
	Rated Power	24W
	Efficiency / Standby power	>80% / <0.3W
	Voltage Tolerance	±5%
	Ripple & Noise	<250mV p-p
	Setup / Rise Time	40ms max.
Input	Hold Up Time	5ms min.
	Rated Voltage	100-240VAC
	Voltage Range	90-264VAC
	Rated Frequency	50/60Hz
	Frequency Range	47-63Hz
	AC Current	0.5A max.
	Inrush Current	40A max. / 240VAC
Protection	Leakage Current	0.25mA / 264VAC
	OCP	Over Current Protection
	SCP	Short Circuit Protection
Environment	Insulation	Insulation class II
	Operating Temperature	0 ~ 40°C
	Storage Temperature	-10 ~ 80°C
	Relative Humidity	25% (0°C) ~ 75% (40°C) RH
Safety & EMC	Storage Relative Humidity	25% (0°C) ~ 75% (40°C) RH
	Safety Standards	CE – EN 60950-1 RoHS
	EMC Emissions	EN 55022:2006+A1:2005 class B EN 55024:1988+A2:2003
	EMC Immunity	EN 61000-3-2:2006, EN 61000-3-3:1995+A1:2001+A2:2005
Others	MTBF	100 000 h
	Dimensions	L76.5 x W34 x H43 mm
	Weight	126g
	Packing	60pcs. / 11kg / carton / L34 x W33 x H37 cm

